## NSN 5306-01-269-9459

Machine Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-01-269-9459

3a
Thread Direction:
Right-hand
Thread Length:
0.390 inches
Fastener Length:
Between 1.063 inches and 1.093 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.204 inches and 0.224 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.359 inches and 0.369 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches primary washer
Material:
Nickel alloy 718
Thread Series Designator:
Unif

## NSN 5306-01-269-9459

Machine Bolt - Page 2 of 2



	ation Data:	Ca	ifi	С	е	3p	٤
--	-------------	----	-----	---	---	----	---

08524-ra22005 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0