NSN 5306-01-269-9459

Machine Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-269-9459

| 3a |
|---------------------------------------|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.390 inches |
| Fastener Length: |
| Between 1.063 inches and 1.093 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.204 inches and 0.224 inches |
| Width Between Flats: |
| Between 0.243 inches and 0.251 inches |
| Extended Washer Diameter: |
| Between 0.359 inches and 0.369 inches |
| Extended Washer Thickness: |
| Between 0.040 inches and 0.060 inches |
| Hole Diameter: |
| Between 0.032 inches and 0.042 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.178 inches and 0.198 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Surface Finish: |
| 32.0 microinches primary washer |
| Material: |
| Nickel alloy 718 |
| Thread Series Designator: |
| Unif |

NSN 5306-01-269-9459

Machine Bolt - Page 2 of 2



| | Spec | cific | ation | Data |
|--|------|-------|-------|------|
|--|------|-------|-------|------|

08524-ra22005 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0