NSN 5306-01-270-1716

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-270-1716

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.541 inches and 0.674 inches **Fastener Length:** Between 1.509 inches and 1.539 inches **Head Style:** Spline extended washer **Head Height:** Between 0.237 inches and 0.287 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.065 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Head Minor Diameter:** Between 0.360 inches and 0.375 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 ty2 cl2 federal standard single treatment response **Thread Series Designator:**

Unjf

NSN 5306-01-270-1716

Shear Bolt - Page 2 of 2



NI/o
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: