
NSN 5306-01-270-4067

Machine Bolt - Page 1 of 2

Thread Class:

3a





Thread Direction: Right-hand Thread Length: Between 0.465 inches and 0.505 inches Fastener Length: Between 0.663 inches and 0.683 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.306 inches and 0.315 inches **Extended Washer Diameter:** 0.360 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches Hole Diameter: Between 0.032 inches and 0.042 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.178 inches and 0.198 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r56400 **Material Specification:** Nas 621 assn standard single material response **Thread Series Designator:** Unjf

NSN 5306-01-270-4067

Machine Bolt - Page 2 of 2



Specification Data:

80205-nas1271 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0