

View Online at <https://aerobasegroup.com/nsn/5306-01-272-3307>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.709 inches and 0.759 inches

Fastener Length:

Between 2.344 inches and 2.374 inches

Head Style:

Spline extended washer

Head Height:

Between 0.327 inches and 0.347 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Hole Diameter:

Between 0.060 inches and 0.070 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Head Minor Diameter:

Between 0.448 inches and 0.455 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches threads

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.