## NSN 5306-01-272-3307

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-272-3307

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.709 inches and 0.759 inches
Fastener Length:
Between 2.344 inches and 2.374 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Hole Diameter:
Between 0.060 inches and 0.070 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.448 inches and 0.455 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Spline
Surface Finish:
32.0 microinches threads
Material:
Steel comp h11

## NSN 5306-01-272-3307

Shear Bolt - Page 2 of 2

A003b0

Mil-c-8837 spec.

Mil-std (military Standard):



Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 type 2 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiia: