NSN 5306-01-272-3417

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-272-3417



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.400 inches and 0.450 inches Fastener Length: Between 4.660 inches and 4.690 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Hole Diameter: Between 0.046 inches and 0.056 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches Grip Length: Between 4.240 inches and 4.260 inches **Hole Quantity:** 3 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate

NSN 5306-01-272-3417

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6704 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0