NSN 5306-01-272-5438

U Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-272-5438

2a Firead Direction: Right-hand Thread Length: 0.750 inches Distance From Inside Center Of Bend To Bolt End: 3.313 inches Thread Diameter: 0.250 inches Thread Value Per Inch (tpl): 2.8 Material: Steal comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification Qap-416 type 2 cl3 federal specification single treatment response Surface Treatment Specification Quep-416 type 2 cl3 federal specification single treatment response Surface Treatment Specification Quep-416 type 2 cl3 federal specification single treatment response Surface Treatment Specification Quep-416 type 2 cl3 federal specification single treatment response Surface Treatment Specification Na Dirto Measure: Na Surface Treatment: Na Surface Treatment Specification single treatment response Surface Treatment: Na Surface Treatment:	Thread Class:
Right-hand Thread Length: 0.750 inches Distance From Inside Center Of Bend To Bolt End: 3.13 inches Thread Distance Between Shanks: 2.126 inches Thread Diameter: 0.250 inches Thread Vap Per Inch (tpi): 2.8 Material: Cadenium and chromate Surface Treatment: Cadenium and chromate Surface Treatment Specification single treatment response Style Designator: Rund Bend Thread Series Designator: Information: Varia Single Treatment: Information: Rund Bend Thread Series Designator: Information:	2a
Tread Length: 0.750 inches Distance From Inside Center Of Bend To Bolt End: 3.313 inches Inside Distance Between Shanks: 2.126 inches Thread Diameter: 0.250 inches Thread Qty Per Inch (tpi): 2.8 Material: Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1010 Steface Treatment Cadmium and chromate Surface Treatment Specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Sheff Life: Na Lift Of Measure: - Thread Series Designator: Into of Measure: - Fig:	Thread Direction:
0.750 inches Distance From Inside Center Of Bend To Bolt End: 3.313 inches 1.516 Distance Between Shanks: 2.126 inches Thread Diameter: 0.250 inches Thread Qty Per Inch (tpi): 28 Material: Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment Qarp-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Sheft Life: N/a Entifice: N/a Did Measure: - Finel Comp Life: N/a Finel Comp Life: N/a Finel Comp Life: N/a Did Measure: - Finel Comp Life: N/a Finel Comp Life: N/a Finel Comp Life: Steel Comp Life: N/a Life: N/a <	Right-hand
Distance From Inside Center Of Bend To Bolt End:3.313 inchesInside Distance Between Shanks:2.126 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Material:Stel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1018 or steel comp 1019 or steel comp 1019 or steel comp 1019 or steel comp 1019 or steel comp 1018 or steel comp 1019 or steel comp 1019 or steel comp 1019 or steel comp 1019 or steel comp 1018 or steel comp 1019 or steel comp 1019 or steel comp 1018 or steel comp 1019 or steel com	Thread Length:
3.313 inchesInside Distance Between Shanks:2.126 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Material:Stel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1019 or steel comp 1019 or steel comp 1018 or steel comp 1019 or steel comp 1018Cadmium and chromateSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseStyle Designator:InfSheff Life:NaLift Measure:InfSheff Life:NaFind Measure:InfFind Measure:InfSheff Life:NaSteries Designator:InfSteries Designator:NaSteries Designator:InfSteries Designator:InfSteries Designator:Steries Designator:InfSteries Designator:InfSteries Designator:InfSteries Designator:InfSteries Designator:InfSteries Designator:InfSteries Designator:InfInfInfInfInfInfInfInfInfInfInfInfInfInfInfInfInfInf <td>0.750 inches</td>	0.750 inches
Inside Distance Between Shanks: 2.126 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Material: Steric Comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qiq-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Urif Sheff Life: N/a Ditt Of Measure: Image: No Fig:	Distance From Inside Center Of Bend To Bolt End:
2.126 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Material:Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qup-416 type 2 cl3 federal specification single treatment responseStyle Designator:Round bendThread Series Designator:UnfShelf Life:N/aUnf for Steel Comp 1014Dist of Measure:Int of Measure:In	3.313 inches
Hread Diameter:0.250 inchesThready Qty Per Inch (tpi):28Material:Stel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020Surface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseGup-416 type 2 cl3 federal specification single treatment responseSurface Series Designator:Round bendSheff Life:NaSheff Life:NaInfor Measure:Femilitarization:Infor Measure:-Fig:Na	Inside Distance Between Shanks:
0.250 inches Thready Qty Per Inch (tpi): 28 Material: Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Q-q-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Sheft Life: N/a Encile Comp Company Part Company	2.126 inches
Thready Qty Per Inch (tpi): 28 Material: Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Sheft Life: N/a Inti Of Measure: - Pomiltarization: Na Fig:	Thread Diameter:
28 Material: Stela comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Shelf Life: N/a Inti Of Measure: - Demiltarization: No Fig:	0.250 inches
Material: Stel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qa-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Shelf Life: N/a Dint Of Measure: - Formiltarization: No Fig:	Thready Qty Per Inch (tpi):
Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl3 federal specification single treatment responseStyle Designator:Round bendThread Series Designator:UnfShelf Life:N/aDint Of Measure:-Demilitarization:NoFig:	28
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Material:
Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl3 federal specification single treatment responseStyle Designator:Round bendThread Series Designator:UnfShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020
Surface Treatment Specification:Qq-p-416 type 2 cl3 federal specification single treatment responseStyle Designator:Round bendThread Series Designator:UnfShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Surface Treatment:
Qq-p-416 type 2 cl3 federal specification single treatment response Style Designator: Round bend Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cadmium and chromate
Style Designator: Round bend Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment Specification:
Round bend Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Qq-p-416 type 2 cl3 federal specification single treatment response
Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Style Designator:
Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No	Round bend
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unf
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A003b0	Fiig:
	A003b0