NSN 5306-01-272-5443

Shear Bolt - Page 1 of 2

Between 0.387 inches and 0.437 inches

Between 2.022 inches and 2.052 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Head Style:

За



View Online at https://aerobasegroup.com/nsn/5306-01-272-5443

Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
0.069 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2 class 2 military specification single treatment response

NSN 5306-01-272-5443

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-8837 spec.