NSN 5306-01-272-7430

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-272-7430

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 1.885 inches and 1.915 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.2016 inches and 0.2026 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas2903 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-272-7430

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0