

View Online at <https://aerobasegroup.com/nsn/5306-01-272-8324>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.300 inches and 0.438 inches

Fastener Length:

Between 1.506 inches and 1.553 inches

Head Style:

Spline drive shear head

Head Height:

0.164 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.448 inches and 0.455 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.385 inches first hole and 1.442 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0