

View Online at <https://aerobasegroup.com/nsn/5306-01-272-8325>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.379 inches and 0.419 inches

**Fastener Length:**

Between 2.226 inches and 2.246 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.189 inches and 0.204 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.688 inches and 1.704 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 630 stand-off or steel comp 631 stand-off

**Material Specification:**

Mil-s-8503 military specification 1st material response fastener or mil-l-6049 military specification 2nd material response fastener or mil-s-5626 military specification 3rd material response fastener or mil-s-6758 military specification 4th material response fastener or mil-s-5000 military specification 5th material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-8503 spec.