

View Online at <https://aerobasegroup.com/nsn/5306-01-272-8325>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.379 inches and 0.419 inches

Fastener Length:

Between 2.226 inches and 2.246 inches

Head Style:

Hexagon

Head Height:

Between 0.189 inches and 0.204 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.688 inches and 1.704 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Surface Finish:

63.0 microinches grip

Material:

Steel comp 630 stand-off or steel comp 631 stand-off

Material Specification:

Mil-s-8503 military specification 1st material response fastener or mil-l-6049 military specification 2nd material response fastener or mil-s-5626 military specification 3rd material response fastener or mil-s-6758 military specification 4th material response fastener or mil-s-5000 military specification 5th material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-8503 spec.