

View Online at <https://aerobasegroup.com/nsn/5306-01-273-2272>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.444 inches and 0.494 inches

Fastener Length:

Between 0.892 inches and 0.922 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Plastic locking feature

Material Specification:

Mil-f-18240 military specification single material response locking feature

Surface Treatment:

Aluminum fastener

Surface Treatment Specification:

Nas4006 assn standard single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6705 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.