NSN 5306-01-273-2273

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-273-2273

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.753 inches and 0.803 inches **Fastener Length:** Between 1.951 inches and 1.981 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.485 inches and 0.500 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 49.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, cl 2 military specification single treatment response **Thread Series Designator:**

Unjf

NSN 5306-01-273-2273

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: