## NSN 5306-01-273-2276

Shear Bolt - Page 1 of 2

Between 0.583 inches and 0.593 inches

Between 1.208 inches and 1.228 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-273-2276

Head Style:
Double hexagon extended washer
Head Height:
Between 0.309 inches and 0.329 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
0.625 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium and chromate
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-273-2276

Shear Bolt - Page 2 of 2



Sp	ecif	icati	ion	Data:

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0