NSN 5306-01-273-2513

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-273-2513 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.758 inches and 0.778 inches **Fastener Length:** Between 3.403 inches and 3.423 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.547 inches and 0.562 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** 0.123 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.740 inches and 2.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Steel comp 4140 or steel comp 4340 or steel comp 6150 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 11, cl 2 military standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 96906-ms21250-08042 government standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-273-2513

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0