

View Online at <https://aerobasegroup.com/nsn/5306-01-273-4383>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.875 inches

Fastener Length:

10.734 inches

Head Style:

Dee chamfer

Head Diameter:

0.375 inches

Head Height:

0.281 inches

Distance From Centerline To Flat:

0.172 inches

First Diameter From Head:

0.250 inches

Second Diameter From Head:

0.188 inches

Third Diameter From Head:

0.250 inches

Fourth Diameter From Head:

0.188 inches

Fifth Diameter From Head:

0.250 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.484 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.188 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.391 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

2.094 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

2.484 inches

Point Style:

Flat

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Externally Relieved Body Diameter Quantity:

11

Err Default:

Err default

Distance From Largest Bearing Surface Of Head To End Of Sixth Diameter:

3.281 inches

Err Default:

Err default

Sixth Diameter From Head:

0.188 inches

Err Default:

Err default

Err Default:

Err default

Special Features:

Plus twelve each alternating undercuts and shoulders of 0.188 and 0.250diameters respectively, distances frombeginning of eleventh diameter from largest bearing surface of head to the end of the twenty-second diameter are 5.422, 5.953, 6.156, 6.688, 7.172, 7.734, 7.938, 8.484, 8.703, 9.203, 9.641, and 9.859

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0