NSN 5306-01-273-6235



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-273-6235 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.922 inches and 0.972 inches **Fastener Length:** Between 2.932 inches and 2.962 inches **Head Style:** Spline drive shear head **Head Height:** 0.539 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole **Head Minor Diameter:** 1.715 inches **Thread Diameter:** 1.125 inches **Grip Length:** Between 1.990 inches and 2.010 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 132000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.648 inches first hole and 2.678 inches first hole **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas672 assn standard single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-273-6235

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0