

View Online at <https://aerobasegroup.com/nsn/5306-01-274-0036>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.476 inches and 1.526 inches

Fastener Length:

Between 4.736 inches and 4.766 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.608 inches and 0.628 inches

Width Between Flats:

Between 0.672 inches and 0.687 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.140 inches and 0.160 inches

Grip Diameter:

Between 0.623 inches and 0.624 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 3.240 inches and 3.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

54800 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.968 inches first hole and 4.018 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Asupply with dog type point 0.499 in. Min and 0.552 in. Max. Diameter; 0.537 in. Nomianl length with groove pin made of 300 derised cres per fed-std-66; apply dry film lubricant to pawl/retainer

Material:

Steel comp xm-13 stand-off

Material Specification:

Astm a580 assn standard 1st material response spring or astm a580 assn standard 2nd material response spring or ams5678 assn standard 3rd material response spring

Surface Treatment:

Passivate stand-off

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stand-off

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0