

View Online at <https://aerobasegroup.com/nsn/5306-01-274-8314>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 3.216 inches and 3.438 inches

Fastener Length:

4.688 inches

Head Style:

Hexagon extended washer

Head Height:

0.624 inches

Width Between Flats:

Between 0.740 inches and 0.750 inches

Extended Washer Diameter:

1.125 inches

Extended Washer Thickness:

0.125 inches

Thread Diameter:

0.875 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

9

Min. Tensile Strength (psi):

125000 pounds per square inch

Special Features:

Supply with dog type point 1.250 in. Long; 0.621 min. Diameter and 0.623 max. Dia.; install spring and balls and stake iaw drawing 4813755, fscm88277 in drilled hole 0.251 min dia. And 0.254 maximum dia. Locaed 0.437 in. From point end

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response and dps9.74, fsc-88277 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.