

View Online at <https://aerobasegroup.com/nsn/5306-01-274-8314>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 3.216 inches and 3.438 inches

**Fastener Length:**

4.688 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

0.624 inches

**Width Between Flats:**

Between 0.740 inches and 0.750 inches

**Extended Washer Diameter:**

1.125 inches

**Extended Washer Thickness:**

0.125 inches

**Thread Diameter:**

0.875 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

9

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Special Features:**

Supply with dog type point 1.250 in. Long; 0.621 min. Diameter and 0.623 max. Dia.; install spring and balls and stake iaw drawing 4813755, fscm88277 in drilled hole 0.251 min dia. And 0.254 maximum dia. Locaed 0.437 in. From point end

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response and dps9.74, fsc-88277 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.