

View Online at <https://aerobasegroup.com/nsn/5306-01-274-8316>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.882 inches and 0.922 inches

Fastener Length:

Between 0.990 inches and 1.010 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.427 inches and 0.447 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

Between 0.080 inches and 0.100 inches

Hole Diameter:

0.070 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.088 inches and 0.108 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0