

View Online at <https://aerobasegroup.com/nsn/5306-01-275-1924>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.611 inches and 0.687 inches

**Fastener Length:**

Between 5.688 inches and 5.734 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

Between 0.553 inches and 0.565 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 5.047 inches and 5.077 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.485 inches first hole and 5.515 inches first hole

**Material:**

Steel comp 321 or steel comp 347

**Material Specification:**

Ams5645 assn standard 1st material response or ams5646 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas501 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0