

View Online at <https://aerobasegroup.com/nsn/5306-01-276-1645>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.395 inches

Fastener Length:

Between 3.802 inches and 3.822 inches

Head Style:

Dished hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Locking Feature:

Retainer grip

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 3.312 inches and 3.328 inches

Features Provided:

Nut

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.692 inches first hole and 3.698 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Also contains plunger located in the thread end of bolt

Material:

Steel comp xm-13 fastener

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0