## NSN 5306-01-277-4339

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-277-4339

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.649 inches and 0.699 inches
Fastener Length:
Between 3.034 inches and 3.064 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.373 inches and 0.374 inches
Head Minor Diameter:
Between 0.423 inches and 0.438 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.365 inches and 2.385 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2, cl 2 military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5306-01-277-4339

Shear Bolt - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.