

View Online at <https://aerobasegroup.com/nsn/5306-01-278-1964>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Fastener Length:

1.968 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.563 inches

Shoulder Diameter:

0.4320 inches first shoulder and 0.4335 inches first shoulder

Shoulder Length:

1.530 inches first shoulder

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.775 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp h11

Material Specification:

Ams 6485 military specification single material response or ams 6487 military specification single material response

Surface Treatment:

Cadmium head and chromate head

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.