

View Online at <https://aerobasegroup.com/nsn/5306-01-278-6622>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.630 inches and 0.690 inches

Fastener Length:

Between 1.115 inches and 1.135 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.240 inches and 0.260 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

First Diameter From Head:

Between 0.165 inches and 0.175 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.435 inches and 0.495 inches

Thread Diameter:

0.190 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Hardness Rating:

42.0 rockwell c and 46.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 601

Material Specification:

Ams6304 uns k14675 assn standard single material response

Surface Treatment:

Cadmium and nickel

Surface Treatment Specification:

Ams2416 assn standard all treatment responses

Supplementary Features:

Aircraft eng and prop. Appl

Thread Series Designator:

Unjf

Specification Data:

96906-ms9208 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0