

View Online at <https://aerobasegroup.com/nsn/5306-01-278-8499>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.740 inches and 0.820 inches

**Fastener Length:**

Between 2.240 inches and 2.260 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.293 inches and 0.313 inches

**Width Between Flats:**

0.312 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**First Diameter From Head:**

Between 0.222 inches and 0.232 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 1.440 inches and 1.500 inches

**Thread Diameter:**

0.250 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Nickel alloy 718

**Material Specification:**

C50tf13 cl-b cagec 07482 mfr ref single material response

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams2410 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0