## NSN 5306-01-280-5718

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-280-5718

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.823 inches and 0.873 inches
Fastener Length:
Between 2.458 inches and 2.488 inches
Head Style:
Spline extended washer
Head Height:
Between 0.383 inches and 0.403 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Hole Diameter:
Between 0.060 inches and 0.070 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.514 inches and 0.521 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Spline
Surface Finish:
32.0 microinches threads
Material:
Steel comp h11

## NSN 5306-01-280-5718

Shear Bolt - Page 2 of 2

A003b0

Mil-c-8837 spec.

Mil-std (military Standard):



Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 type 2 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: