NSN 5306-01-280-5723

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Thread Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-280-5723

Between 0.649 inches and 0.699 inches **Fastener Length:** Between 1.909 inches and 1.939 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Head Minor Diameter:** Between 0.423 inches and 0.438 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, class 3 military specification single treatment response **Thread Series Designator:** Unjf

NSN 5306-01-280-5723

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: