NSN 5306-01-280-5724

Shear Bolt - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-280-5724

Inread Direction:	
Right-hand	
Thread Length:	
Between 0.566 inches and 0.699 inches	
Fastener Length:	
Between 2.221 inches and 2.251 inches	
Head Style:	
Spline extended washer	
Head Height:	
Between 0.327 inches and 0.347 inches	
Extended Washer Diameter:	
Between 0.691 inches and 0.701 inches	
Extended Washer Thickness:	
Between 0.044 inches and 0.064 inches	
Grip Diameter:	
Between 0.3735 inches and 0.3745 inches	
Head Minor Diameter:	
Between 0.423 inches and 0.438 inches	
Thread Diameter:	
0.375 inches	
Grip Length:	
Between 1.552 inches and 1.572 inches	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hardness Rating:	
46.0 rockwell c and 50.0 rockwell c	
Surface Finish:	
32.0 microinches grip	
Material:	
Steel comp h11	
Material Specification:	
Ams 6487 assn standard single material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Mil-c-8837, type 2, class 2 military specification single treatment response	
Thread Series Designator:	
Unjf	

NSN 5306-01-280-5724

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: