NSN 5306-01-280-5725

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-280-5725

Thread Length:
Between 0.653 inches and 0.803 inches
Fastener Length:
Between 2.701 inches and 2.731 inches
Head Style:
Spline extended washer
Head Height:
Between 0.383 inches and 0.403 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.485 inches and 0.500 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.928 inches and 1.948 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2, class 2 military specification single treatment response
Thread Series Designator:
Unjf

NSN 5306-01-280-5725

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: