## NSN 5306-01-280-5727

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-280-5727



Thread Class:

3a

**Thread Direction:** 

Right-hand

Thread Length:

Between 0.884 inches and 0.945 inches

#### Fastener Length:

Between 3.693 inches and 3.723 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.552 inches and 0.572 inches

#### **Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

#### **Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

#### **Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

#### Head Minor Diameter:

Between 0.673 inches and 0.688 inches

#### Thread Diameter:

0.625 inches

Grip Length:

Between 2.678 inches and 2.698 inches

#### Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

#### Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

#### Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

#### **Material Specification:**

Ams 6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5306-01-280-5727

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

### Mil-std (military Standard):

Mil-c-8837 spec.

