

View Online at <https://aerobasegroup.com/nsn/5306-01-280-6688>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

3.000 inches

**Eye Inside Diameter:**

Between 0.315 inches and 0.321 inches

**Shoulder Thickness:**

3.940 inches

**Shank Length:**

4.560 inches

**Eye Stock Thickness:**

Between 0.229 inches and 0.239 inches

**Shoulder Diameter:**

0.812 inches

**Overall Length:**

9.500 inches

**Thread Diameter:**

0.500 inches

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Distance From Center Of Eye To Shank End:**

9.025 inches

**Eye Outside Width:**

0.812 inches

**Special Features:**

Solid film lubricant on head area only

**Color:**

Green first shoulder and gray first shoulder and white first shoulder

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Primer first shoulder and paint first shoulder

**Surface Treatment Specification:**

Mil-p-24441/1 military specification 1st treatment response first shoulder and mil-p-24441/2 military specification 2nd treatment response first shoulder and mil-p-24441/3 military specification 2nd treatment response first shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.