

View Online at <https://aerobasegroup.com/nsn/5306-01-280-6688>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

3.000 inches

Eye Inside Diameter:

Between 0.315 inches and 0.321 inches

Shoulder Thickness:

3.940 inches

Shank Length:

4.560 inches

Eye Stock Thickness:

Between 0.229 inches and 0.239 inches

Shoulder Diameter:

0.812 inches

Overall Length:

9.500 inches

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Center Of Eye To Shank End:

9.025 inches

Eye Outside Width:

0.812 inches

Special Features:

Solid film lubricant on head area only

Color:

Green first shoulder and gray first shoulder and white first shoulder

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Primer first shoulder and paint first shoulder

Surface Treatment Specification:

Mil-p-24441/1 military specification 1st treatment response first shoulder and mil-p-24441/2 military specification 2nd treatment response first shoulder and mil-p-24441/3 military specification 2nd treatment response first shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.