NSN 5306-01-280-6721

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-280-6721

view Offilite at https://defobasegroup.com/hsr//3500-01-250-0721
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.429 inches and 0.479 inches
Fastener Length:
Between 1.877 inches and 1.907 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Paraitata

Passivate

NSN 5306-01-280-6721

Shear Bolt - Page 2 of 2



Surface Treatment Specification:
Nas 4003 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6306 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A003b0

Demilitarization: