

View Online at <https://aerobasegroup.com/nsn/5306-01-281-0556>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.690 inches and 0.810 inches

Distance From Inside Center Of Bend To Bolt End:

1.365 inches

Inside Distance Between Shanks:

0.490 inches

Thread Diameter:

0.250 inches

Thread Qty Per Inch (tpi):

20

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1214 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330 or steel comp 1046 or steel comp 1049 or steel comp 1053 or steel comp 1055 or steel comp 1060 or steel comp 1070 or steel comp 1078 or steel comp 1080 or steel comp 1084 or steel comp 1090 or steel comp 1095 or steel comp 1524 or steel comp 1536 or steel comp 1541 or steel comp 1548 or steel comp 1551 or steel comp 1552 or steel comp 1566 or steel comp 1572

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Style Designator:

Round bend

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0