

View Online at <https://aerobasegroup.com/nsn/5306-01-281-2334>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.827 inches and 0.877 inches

Fastener Length:

Between 2.025 inches and 2.055 inches

Head Style:

Spline extended washer

Head Height:

Between 0.440 inches and 0.460 inches

Extended Washer Diameter:

Between 0.923 inches and 0.932 inches

Extended Washer Thickness:

Between 0.062 inches and 0.082 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Head Minor Diameter:

Between 0.644 inches and 0.651 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 1.178 inches and 1.198 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.