## NSN 5306-01-282-2363

Machine Bolt - Page 1 of 2

Between 0.740 inches and 0.820 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-282-2363

Between 1.052 inches and 1.072 inches
Head Style:
Hexagon
Head Height:
Between 0.240 inches and 0.260 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
Between 0.060 inches and 0.080 inches
End Application:
Spec item
Thread Diameter:
0.250 inches
Grip Length:
Between 0.252 inches and 0.312 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Hole Configuration Style:
Hexagon longitudinal hole
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response

## NSN 5306-01-282-2363

Machine Bolt - Page 2 of 2



Thread Series Designate	or:
-------------------------	-----

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0