

View Online at <https://aerobasegroup.com/nsn/5306-01-282-4790>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.441 inches and 0.508 inches

Fastener Length:

Between 1.326 inches and 1.373 inches

Head Style:

Spline drive shear head

Head Height:

Between 0.177 inches and 0.197 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.202 inches first hole and 1.259 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0