## NSN 5306-01-283-1752

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-283-1752

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.995 inches and 1.045 inches **Fastener Length:** Between 4.067 inches and 4.097 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.623 inches and 0.624 inches **Head Minor Diameter:** Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 3.052 inches and 3.072 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 3 military specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-283-1752

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Shelf Life:

Mil-std (military Standard):

Mil-c-8837 spec.