

View Online at <https://aerobasegroup.com/nsn/5306-01-283-2420>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.672 inches and 0.831 inches

**Fastener Length:**

Between 1.102 inches and 1.122 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.375 inches and 0.385 inches

**Internal Drive Style:**

Hexagon

**End Application:**

F-16, eagle f-15, lantirn

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.1409 inches and 0.1426 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

72 slots on thread end 0.125-0.140 in. Dia.; 0.620 in. Lg. For lockwire; 2 long slots on threads and shank 0.045-0.055 in. Dia.; lockwire 17-7ph cres per ams 5673 heat treated to condition ch900 per mil-h-6875, passivated per qq-p-35; threads 2 lead

**Material:**

Iron alloy 660 fastener

**Material Specification:**

Ams 5732 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0