## NSN 5306-01-283-3595

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-283-3595

Qq-p-35 federal specification single treatment response fastener

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.884 inches and 1.016 inches
Fastener Length:
Between 0.984 inches and 1.016 inches
Head Style:
Spline extended washer
Head Height:
Between 0.492 inches and 0.500 inches
Extended Washer Diameter:
Between 0.735 inches and 0.750 inches
Extended Washer Thickness:
Between 0.177 inches and 0.197 inches
Locking Feature:
Pellet threads or patch threads or strip threads
Head Minor Diameter:
Between 0.485 inches and 0.500 inches
Thread Diameter:
0.500 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Steel comp 302 fastener or steel comp 303 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:

## NSN 5306-01-283-3595

Machine Bolt - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	<b>D</b> C3	igilatoi.

Unf

**Specification Or Standard:** 

1 type and 11 style

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0