

View Online at <https://aerobasegroup.com/nsn/5306-01-284-0843>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.821 inches and 0.861 inches

**Fastener Length:**

Between 2.393 inches and 2.413 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.494 inches and 0.514 inches

**Width Between Flats:**

0.563 inches

**Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

**Extended Washer Thickness:**

Between 0.113 inches and 0.133 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.552 inches and 1.572 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Product Name:**

Navy special project

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-8844 cl 1 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2401-3 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-8844 spec.