NSN 5306-01-284-5256

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-284-5256 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** Between 0.605 inches and 0.635 inches **Head Style:** Flat countersunk **Head Diameter:** 0.508 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches Single Shear Strength: 95000 pounds per square inch **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Because of material and plating, bolt is identified w/red dye or paint on the thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-01-284-5256

Shear Bolt - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0