

View Online at <https://aerobasegroup.com/nsn/5306-01-284-8100>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.514 inches and 0.574 inches

**Fastener Length:**

Between 1.279 inches and 1.309 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Primary Washer Outside Diameter:**

0.480 inches

**Primary Washer Style:**

Finishing

**Primary Washer Material Thickness:**

0.032 inches

**Special Features:**

Bolt furnished with tab, material cres comp 301 per mil-s-5059, finish passivated per qq-p-35

**Material:**

Steel comp 303se stand-off

**Material Specification:**

Mil-s-5059 military specification single material response primary washer

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.