

View Online at <https://aerobasegroup.com/nsn/5306-01-284-8102>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.376 inches and 0.451 inches

Fastener Length:

Between 0.453 inches and 0.498 inches

Head Style:

Hexagon

Head Height:

0.155 inches

Width Between Flats:

Between 0.428 inches and 0.440 inches

Locking Feature:

Strip threads

Thread Diameter:

0.190 inches

Grip Length:

Between 0.047 inches and 0.077 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Product Name:

Navy special project

Special Features:

Plastic polytetrafluoroethylene primary washer rubber butadiene-acrylonitrile class nbr ring

Material:

Steel comp 410 fastener or steel comp 431 fastener

Material Specification:

Mil-p-25732 military specification single material response ring

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-25732 spec.