

View Online at <https://aerobasegroup.com/nsn/5306-01-284-8102>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.376 inches and 0.451 inches

**Fastener Length:**

Between 0.453 inches and 0.498 inches

**Head Style:**

Hexagon

**Head Height:**

0.155 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Locking Feature:**

Strip threads

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.047 inches and 0.077 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Product Name:**

Navy special project

**Special Features:**

Plastic polytetrafluoroethylene primary washer rubber butadiene-acrylonitrile class nbr ring

**Material:**

Steel comp 410 fastener or steel comp 431 fastener

**Material Specification:**

Mil-p-25732 military specification single material response ring

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-p-25732 spec.