## NSN 5306-01-284-8106

Externally Relieved Body Bolt - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5306-01-284-8106            |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 2.000 inches   |
| Fastener Length:   |
| 4.600 inches   |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| 0.400 inches   |
| Width Between Flats:   |
| Between 0.865 inches and 0.877 inches                                    |
| First Diameter From Head:  |
| Between 0.560 inches and 0.562 inches                                    |
| Second Diameter From Head:   |
| Between 0.467 inches and 0.477 inches                                    |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:  |
| 2.430 inches   |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 2.600 inches   |
| Thread Diameter:   |
| 0.563 inches   |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Externally Relieved Body Diameter Quantity:                              |
| 1  |
| Material:  |
| Steel comp 440c  |
| Material Specification:  |
| Qq-s-763 cond a federal specification single material response           |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A003b0